



Zone-Flex 8

8mm x 1000mm x 1000mm

Zone-Flex 10

10mm x 1000mm x 1000mm

Applications: Commercial gyms and leisure centres, free weights and cross-fit areas. Provides shock absorption and impact sound reduction.

ECO-TEK advanced flooring solutions are designed to reduce impact sound transmission and vibration caused by free weights and cardio gym equipment. The result is a safe exercise space that causes minimal noise disturbance for adjacent spaces.

High performance adhesive free tiles with precise dovetail interlocking profile. Zone-Flex 8 and Zone-Flex 10 tiles offer enhanced shock absorption and a safe resilient platform for exercises. The premium vertical locking mechanism allows easy installation and complete flexibility. This interlocking floor system provides a totally adhesive free installation process, preventing contamination of the subfloor.

Principle Features

- **Adhesive free** - No adhesive contamination of the subfloor with vertical interlocking system.
- **Flexible** - Areas can be re-purposed at any time by simply disconnecting the tiles and refitting.
- **Acoustic Performance** - Excellent impact sound reduction.
- **Sustainable and Recyclable** - Manufactured using recycled rubber.
- **Healthy Environment** - Superfine compounds reduce absorption of dirt and make the cleaning process easier. Hygienic, SBR rubber is naturally anti-microbial, anti-allergy.



Product Benefits

- Adhesive free interlocking installation system with vertical disassembly.
- No adhesive contamination of the subfloor.
- Anti-fatigue, impact force resistant flooring.
- Provides a safe exercise platform, sound insulation and shock absorption from free weight activities.
- Gym flooring is made from recycled rubber from used vehicle tyres, preventing these materials from becoming waste and landfill.

Applications

- Commercial gyms.
- Spin rooms.
- Equipment isolation.
- Cross fit training areas.
- Yoga studios.

Zone-Flex Product Range

Thickness	Zone-Flex 8 - 8mm Zone-Flex 10 - 10mm
Dimensions	500mm x 500mm
Density	900 kg/m
Impact Sound Reduction	Zone-Flex 8 - 19dB Zone-Flex10 - 19dB

Further acoustic improvements can be achieved by combining with ISO-Flex multi-layer systems.

Colour Options

- 15% EPDM Coloured Flecks
- Dark Grey Fleck
- Blue Fleck
- Light Grey Fleck
- Red Fleck

